



Phantom Pursuit Rules - SAM 35 Rules, 2017 Onwards

THE AIMS:

A rebirth of this once very popular competition. Longer lines should help older pilots and make racing safer. Launch will be at the Old Warden Mayfly 2017

The Model :

- a) Phantom Mk11 built to the original KK plan outline
- b) Bellcrank must be fitted to engine bearers.
- c) Fuselage sides may be reinforced with 1/32" ply.
- d) Wing leading edges may be reinforced with inset ply.
- e) Wing to be set at 0 degree incidence.
- f) Flexible Heavy Weight leadouts.
- g) Pilot in cockpit.
- h) BMFA registration number on inboard wing.
- i) 1/3/4" spinner
- j) Tail Skid may be fitted
- k) Fin may be fitted without offset.
- l) Wingtip weight to be fitted to outside wing (Suggest inset in wing).
- m) 2" Racing Wheels
- n) Engine: 1.5cc steel liner may be plain, single or twin ball race.
- o) Propeller: standard commercial propeller for i.c.use dimensions to suit engine (no electric type).
- p) Tank - No limit to tank size and a cut out may be fitted.
- q) Racing number may be shown on fin.
- r) Lines .012" 45' from centre line of handle to centre line of fuselage.

FLYING :

- a) Wrist straps to be fitted.
- b) 100 lap heats two up with two mandatory pit stops.
- c) 200 lap final two/three up with five mandatory stops.

AWARDS :

Certificate for the three finalists

BL 8^h August 2016. Sponsor: ReviewerName Brian Lever. Reviewed 08/08/2016